

VoTELPBX E100/200



VoTELPBX E100/200 offers SMBs cost effective additions to legacy telephone systems to bring the true benefits of VoIP. E100/200 is a single or dual port VoIP E1/T1/J1 gateway (VoIP to E1/T1/J1, and E1/T1/J1 to VoIP) that supports up to 30 or 60 concurrent calls. It's designed to bridge the gap between E1/T1/J1 and VoIP networks. Integrating E100/200 into an existing network will allow inexpensive communication via SIP trunking. Also, it could connect VoIP systems with E1/T1/J1 service from legacy carriers.

Specifications

- ☒ E1/T1/J1 port: 1/2 (Support PRI, MFC R2, SS7)
- ☒ Protocol: SIP(RFC3261)
- ☒ DTMF: RFC2833, SIP Info, In-band.
- ☒ Codec: G711a, G711u, G.722, G.726, G.729a, GSM, Speex, ADPCM
- ☒ TE100 Ethernet interfaces:
 - 1 10/100 Mbps LAN
 - 1 10/100 Mbps WAN
- ☒ TE200 Ethernet interfaces:
 - 1 10/100/1000 Mbps LAN
 - 1 10/100/1000 Mbps WAN
- ☒ Size: 213x160x44 mm
- ☒ Weight: 1.2 kg
- ☒ Power: AC 100-240V, 50-60HZ

Features

- ☒ Trunk support
- ☒ Call routing rules
- ☒ Automatic appending and stripping of digits to dialed numbers
- ☒ Caller ID name and number support
- ☒ FAX support
- ☒ Blacklist
- ☒ Firewall
- ☒ DDNS Support
- ☒ Backup and Restore

Benefits

- ☒ Cost-effective call routing rules
- ☒ Easy-to-navigate GUI
- ☒ Simple installation
- ☒ Easy to integrate
- ☒ Low power consumption for your green office